

Benchtop • High Speed • Ventilated • Centrifuge

T16-M



Scan to watch product video




16500 rpm	Maximum Speed
23120 xg	Maximum RCF
4x100 ml	Maximum Capacity
≤ 58dB (A)	Noise Level(dBA)

Technical Specifications:

Time range	0-99minutes adjustable	Speed accuracy	±10r/min
Motor	Frequency Converter motor	Display	LCD
Power supply	AC220V,50HZ,5A,600W	Acceleration /Deceleration rates	0--10
Dimension	470x345x295mm(LxWxH)	Weight without rotor	28kg

Matched Rotors

No.	Rotor	Capacity	Max.speed	Max. RCF	Note
NO.1 	Angle rotor	12×1.5/2.2ml	16500r/min	19175xg	PP/PC tube
	Adapter	12×0.5/0.2ml			PP/PC tube
NO.2 	Angle rotor	12×5ml	16500r/min	19480xg	PP/PC tube
	Adapter	12×1.5ml			PP/PC tube

NO.3 	Angle rotor	12×10ml	12000r/min	13156xg	PP/PC tube
	Adapter	12×5ml			PP/PC tube
NO.4 	Angle rotor	24×1.5/2.2ml	14000r/min	17530xg	PP/PC tube
	Adapter	24×0.5/0.2ml			PP/PC tube
NO.5 	Angle rotor	36×1.5/2.2ml	13000r/min	15400xg	PP/PC tube
	Adapter	36×0.5/0.2ml			PP/PC tube
NO.6 	Angle rotor	12×8×0.2ml	15000r/min	23120xg	PCR 8-tube strips
NO.7 	Angle rotor	10×15ml	11000r/min	14745xg	PP/PC tube
	Adapter	10×10ml			PP/PC tube
	Adapter	10×5ml			PP/PC tube
NO.8 	Angle rotor	6×50ml	11000r/min	12175xg	PP/PC tube
	Adapter	6×15/10ml			PP/PC tube
	Adapter	6×1.5ml			PP/PC tube
NO.9 	Angle rotor	4×10/100ml	10000r/min	10975xg	PP/PC tube
	Adapter	4×50ml			PP/PC tube
	Adapter	4×15/10ml			PP/PC tube
	Adapter	4×5/1.5ml			PP/PC tube